Mnova Publications File Format (.mnpub) v1.0

1. INTRODUCTION

The Mnova publications file format, allows to selected publishers to view and analyze the publication datasets with Mnova. The publishers must use a RSA key pair. The public key must be send to Mestrelab and Mestrelab will generate a certificate file (with extension mncrt). Once the publisher get the mncrt file it will use his private RSA key to sign their dataset getting a signature. With the signature, the certification file (mncrt) and a URL to the signed dataset a mnpub file is composed. Mnova will read the mnpub and will verify with the public key information contained in the mnpub file the dataset pointed by the URL field of the mnpub file.

2. GENERAL CONSIDERATIONS

mnpub is a text file encoded with UTF-8. The line end can be either LF (Unix) or CR LF (Windows) and it can have a maximum length of 2048 characters.

- 3. FORMAT
- 3.1 HEADER

The file starts with the mandatory header line:

---- MNOVA PUBLICATIONS FILE -----

3.2 LINE SYNTAX

The next text lines to the header line must follow the syntax:

KEY:VALUE

The KEY part cannot contain the semicolon character ':'. The VALUE member can have any valid UTF-8 character. Spaces at the beginning and end of the line, and at the beginning and end of KEY and VALUE are igonred, so the line:

KEY : VALUE

would be equivalent to the previous one and valid. Empty lines are skipped.

3.3 CONTENTS

For	the current	version the predefined KEY values are	:
	PUBKEY	(mandatory)	
	PUBKEY ID	(optional)	
	PUBKEY_SIGN	(mandatory)	
	SIGNATURE	(mandatory)	
	URL	(mandatory)	

3.3.1 PUBKEY

This field is mandatory and it contains the public key used to sign the data pointed by the URL field. The PUBKEY it will be generated from the publisher's public key by Mestrelab and send it back to the publisher in the certificate file (mncrt file).

3.3.2 PUBKEY_ID

It contains the public key ID and the field is not mandatory. It's just to know the ID given by Mestrelab to the publisher's public key. The PUBKEY_ID it will be generated from the publisher's public key by Mestrelab and send it back to the publisher in the certificate file (mncrt file).

3.3.3 PUBKEY_SIGN

This field is mandatory and it contains the public key signature used to verify that the public key of the publisher was granted by Mestrelab. The PUBKEY_SIGN it will be generated from the publisher's public key by Mestrelab and send it back to the publisher in the certificate file (mncrt file).

3.3.4 SIGNATURE

The signature field must exist and it will contain the signature of the file pointed by the URL field. The signature will be represented in base64 and in a single line (Split it in several lines is not allowed). For example:

SIGNATURE:M4EUJd50pqHMt41oAIGlssLTx152CIZZSUjHHeaIU9z5Qd2W0QtZSbfdZh500gVfn...

NOTE: In the example above, we have truncated the signature base64 text and we are ending the field with '...' meaning that more text will go there.

3.3.5 URL

The URL field must exist and it will contain either a valid URL or a relative path to the data file (relative to the mnpub file). Examples:

http://servername.org/path/to/file/data.zip file:///path/to/another file/data.zip file:///C:/windows/path/data.zip data.zip relative/path/data.zip

NOTE: As the mnpub file uses UTF-8 enconding, it's no needed and it's not supported to use percent enconding for the URL value. So, the URL $\ensuremath{\mathsf{VRL}}$

http://servername.org/path%20with%20spaces/data.zip

is not supported and it should look like:

http://servername.org/path with spaces/data.zip

4. Changelog

	AUTHOR	VERSION	DATE
Felipe Seoa	ne (fseoane@mestrelab.com)	1.0	2016/02/11